# Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.

# 70L 90L 100L Carbon Steel Fm200 Nitrogen Gas Cylinder For 4.2MPa / 5.6MPa Fire Suppression System

#### **Basic Information**

• Place of Origin: Guangzhou, GuangDong, China

Brand Name: RUIGANG

Certification: CCC/ISO9001/ISO14001/ISO10012/ISO45001

Model Number: 70L/90L/100L/120L/150L/180L

Minimum Order Quantity: 2set system Price: negotiation

• Packaging Details: Plywood outer box with bubble bag or pape

• Delivery Time: 15~20 working days

Payment Terms:
 L/C, T/T, Western Union, Paypal, Credit card

• Supply Ability: 30000 sets per month



### **Product Specification**

• Capacity: 70L/90L/100L/120L/150L/180L

• Color: Red

Filling Medium: FM200+nitrogenMaterial: Carbon Steel

• Highlight: 70I gas cylinder, 70I fire suppression system,

90l gas cylinder



#### **Product Description**

#### Red Color Fm200 Gas Cylinder For 4.2 / 5.6MPa Fire SuppressionSystem

The fm200 gas cylinder is made with carbon steel and used to store the fm200 agent that is in liquid condition. This cylinder is different in size, volume as well as the storage pressure. No matter which size of cylinder, there are only two kinds of storage pressures -- 4.2MPa and 5.6MPa. Besides, all these cylinders can be used in all kinds of fire suppression system not just for fm200 fire suppression system.

#### Cylinder Parameter

| Symiaer rarameter  |              |                                    |  |   |  |  |
|--|--------------|------------------------------------|--|---|--|--|
| 70L  | 90L          | 100L                               | 120L   | 150L  | 180L   | 180L   |
| 350  | 350          | 350                                | 350  | 400   | 400  | 450  |
| 911±5  | 1119±5       | 1221±5                             | 1429±5   | 1388±5  | 1630±5   | 1328±5   |
| FM200+nitrogen   |              |                                    |  |   |  |  |
| 950kg/m <sup>3</sup>                                     |              |                                    |  |   |  |  |
| GB6653-2008  |              |                                    |  |   |  |  |
| 6.3  | 6.3          | 6.3                                | 6.3  | 6.3   | 7.2  | 7.7  |
| C≤0.20% Si≤0.35% Mn≤1.50%<br>P≤0.025% S≤0.015% P+S≤0.04% |              |                                    |  |   |  |  |
| Rm 510~620MPa<br>Rel ≥345MPa                             |              |                                    |  |   |  |  |
| 8.4MPa   |              |                                    |  |   |  |  |
| 5.6MPa   |              |                                    |  |   |  |  |
|  | 350<br>911±5 | 350 350<br>911±5 1119±5<br>6.3 6.3 | 350 350 350<br>911±5 1119±5 1221±5<br>FM  G  6.3 6.3 6.3  C≤0.20% P≤0.025% S | 350 350 350 350 350 911±5 1119±5 1221±5 1429±5  FM200+nitrog 950kg/m³ GB6653-200 6.3 6.3 6.3 6.3  C≤0.20% Si≤0.35% P≤0.025% S≤0.015%  Rm 510~620M Rel ≥345MF 8.4MPa | 350 350 350 350 400  911±5 1119±5 1221±5 1429±5 1388±5  FM200+nitrogen  950kg/m³  GB6653-2008  6.3 6.3 6.3 6.3 6.3 6.3  C≤0.20% Si≤0.35% Mn≤1.50% P≤0.025% S≤0.015% P+S≤0.049  Rm 510~620MPa Rel ≥345MPa  8.4MPa | 350 350 350 350 400 400  911±5 1119±5 1221±5 1429±5 1388±5 1630±5  FM200+nitrogen  950kg/m³  GB6653-2008  6.3 6.3 6.3 6.3 6.3 7.2   C≤0.20% Si≤0.35% Mn≤1.50% P≤0.025% S≤0.015% P+S≤0.04%  Rm 510~620MPa Rel ≥345MPa  8.4MPa |



The bottle part is composed of steel cylinder and cylinder valve

## Why Choose Us

100,000 sq.meter working plant

More reliable patented technologies

Intelligent production and advanced management Professional R&D team and product testing centers Complete product range

Fast solution design and quick delivery.

We provide 8×6 hrs technical support and service.

We always pack it with polyfoam firstly and then put it into a wooden case. Sometimes, in order to meet with customers or the safety requirement, we will make a pallet for the goods.





#### **Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.**



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou