

23 广州瑞老海防治会有周公司

HFC-227ea Automatic Ceiling Fire Extinguisher Maximum Protective Volume 36 Cubic Meter

Basic Information

• Place of Origin: Guangzhou, Guangdong, China

Brand Name: RUIGANG

Certification: CCC/ISO/CMA/CAL/CNAS

Model Number: XQQC20/1.6RG

 Minimum Order Quantity: 3 set

• Price:

negotiation

Packaging Details:

Plywood outer box with bubble bag or paper

Delivery Time:

10~15 working days

• Payment Terms:

L/C, D/P, T/T, Western Union, Paypal, Credit

card

• Supply Ability: 30000 sets / month



Product Specification

• Discharge Time: ≤10s

Extinguishing Agent: HFC-227eaInstallation: Easy To Install

• Cylinder Heigh: 468±20(mm)

Agent: HFC-227ea(FM200)

Maximum Protective

Volume:

36 Cubic Meter

• Working Pressure: 1.6MPa

 Ambient Working Temperature: 0°C 50°C

 Outside Diameter Of Cylinder: Ф350mm

Maximum Filling

1 Kg/L

Density:



Product Description

Effortless Installation HFC-227ea Automatic Fire Extinguisher

Product Description:

The Automatic Fire Extinguisher is designed to operate within a wide range of temperatures, making it reliable and effective in various environments. It can withstand temperatures ranging from 0°C to 50°C, ensuring that it is ready to use whenever and wherever it is

The Automatic Fire Extinguisher is equipped with a hanging device that makes it easy to install and use. It can be hung from the ceiling, ensuring that it is easily accessible and visible to everyone. This hanging device also ensures that the fire extinguisher is out of reach of children and pets, making it a safer option for fire protection.

The Automatic Fire Extinguisher is equipped with FM200, a highly effective fire suppression agent that is widely used in the industry. FM200 is a clean agent that does not leave any residue, making it an ideal choice for protecting sensitive equipment and electronics. The FM200 Hanging System is designed to quickly and effectively extinguish fires, preventing them from spreading and causing further

With a discharge time of less than 10 seconds, the Automatic Fire Extinguisher is designed to guickly and effectively extinguish fires. This fast response time ensures that fires are put out before they can cause significant damage, protecting your property and keeping you and

In conclusion, the Automatic Fire Extinguisher, model XQQC20/1.6RG, is a reliable and effective fire protection solution that is designed to quickly and efficiently extinguish fires. It is equipped with an electric actuated driving mode, a working pressure of 1.6MPa, and can operate within a wide range of temperatures. It is also equipped with a hanging device and FM200, making it a safer and more effective option for fire protection. With a discharge time of less than 10 seconds, it is a fast-acting fire extinguisher that ensures that fires are put out before they can cause significant damage.

Features:

Product Name: FM200 Automatic fire extinguisher

Fire Extinguisher Color: Red

Working Temperature Range: 0°C~50°C

Cylinder Height: 468±20(mm)

Cylinder Color: Red Volume: 20L Features:

Hanging fire extinguisher

The HFC-227ea hanging extinguishing device The hanging fm200 automatic fire extinguisher

Technical Parameters:

Extinguishing Agent	HFC-227ea (FM200)
Cylinder Color	Red
Fire Extinguisher Color	Red
Working Tempreture Range	0°C~50°C
Working Pressure	1.6MPa
Diameter	350±20(mm)
Maximum protective volume	36 Cubic Meter
Driving mode	Electric Actuated
Installation mode	Hanging

Applications:

The Automatic Fire Extinguisher is designed to be used in various situations and occasions. It can be used in residential buildings, commercial establishments, warehouses, factories, and other places that require fire protection. It is perfect for places where fires can start easily, such as kitchens, electrical rooms, and server rooms. It is also ideal for places where people are not always present, such as storage rooms and parking lots.

The Automatic Fire Extinguisher is very easy to install, thanks to its electric actuated driving mode. It can be installed quickly and easily in any location without the need for any special tools or equipment. The extinguisher has a maximum working pressure of 2.5MPa, which means it can handle even the toughest fires.

The Automatic Fire Extinguisher uses HFC-227ea(FM200) as the agent for extinguishing fires. FM200 is a colorless, odorless, and electrically non-conductive gas that is safe for humans and the environment. The HFC-227ea hanging device is designed to hang in an area where fires are most likely to occur. It is activated when the temperature reaches a certain level, and it can extinguish the fire in less than 10 seconds

The Automatic Fire Extinguisher comes with a plywood outer box with a bubble bag or paper for packaging. The minimum order quantity is 3 sets, and the price is negotiable. Delivery time is 10-15 working days, and payment terms include L/C, D/P, T/T, Western Union,

Paypal, and Credit card. The supply ability is 30000 sets per month, making it readily available for customers who need it.

Support and Services:

Our automatic fire extinguisher product is designed to provide reliable and effective fire protection in a variety of settings. To ensure optimal performance, we offer the following technical support and services:

- Installation assistance and consultation
- Product training and education
- Troubleshooting and maintenance support
- Replacement parts and accessories
- Warranty and repair services

Our team of experienced professionals is dedicated to helping you achieve the highest level of fire safety and protection. Contact us today to learn more about how we can assist you with your fire extinguisher needs.



Packing and Shipping:

Product Packaging:

1 Automatic Fire Extinguisher

Mounting Bracket

Installation Instructions

Shipping:

Shipped via standard ground shipping



Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou