

Automated Start IG100 Inert Gas Fire Suppression System 20MPa DC24V

Basic Information

- Place of Origin: Guangzhou, Guangdong, China
- Brand Name: RUIGANG
- Certification: CCC/ISO/CMA/CAL/CNAS
- Model Number: QMD20/90-RG
- Minimum Order Quantity: 1 set
- Price: negotiation
- Packaging Details: Plywood outer box with bubble bag or paper
- Delivery Time: 10~15 working days
- Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card
- Supply Ability: 3000 sets per week



Product Specification

- System Power Supply: DC24V/1.6A
- Shipping Way: By Sea
- Agent: Nitrogen
- Min Working Pressure: 18MPa
- Working Temperature: 0°C ~ +50°C
- Working Pressure: 20MPa
- Actuation: Automatic Or Manual Start
- Trademark: RUIGANG
- Outside Diameter Of Cylinder: $\Phi 279 \pm 10 \text{mm}$
- Height Of Cylinder: $1826 \pm 10 \text{mm}$
- Cylinder Volume: 90L
- Color: Red

Product Description

Automated Start IG100 Inert Gas Fire Suppression System 20MPa Working Pressure DC24V Power Supply

Product Description:

The Inert Gas Fire Extinguishing System comes with a weight of 25.3KG, making it easy to install and maintain. The system has a discharge time of $\leq 60S$, ensuring that the fire is quickly extinguished, minimizing damage to your property and reducing downtime. The system is designed to work in temperatures ranging from 0°C to +50°C, making it suitable for use in a variety of environments. The Inert Gas Fire Extinguishing System is packed in a sturdy wooden box, ensuring that it is protected during transportation. The system is easy to install and can be customized to meet the specific needs of your property. The system is equipped with safety features that ensure that the concentration of the inert gas is $\leq 52\%$, ensuring that the system is safe for use in occupied areas. The Inert Gas Fire Extinguishing System is an ideal solution for protecting your property from fire. The system is efficient, reliable, and eco-friendly, making it the perfect choice for sensitive areas. With its fast discharge time and easy installation, the system ensures that your property is safe in the event of a fire. Invest in the Inert Gas Fire Extinguishing System today and ensure the safety of your property.

Features:

Product Name: Inert Gas Fire Suppression System

Transport Package: Wooden Box

Weight of agent: 25.3KG

Storage Bottle Material: Steel Gas Cylinder

High Light: IG100 Fire Suppression System / Non-polluting Inert Gas Fire Extinguishing System

Activation Method: Automatic / Manual Operation

This Inert Gas Fire Suppression System is a highly effective Fire Extinguishing System that uses IG100 inert gas to extinguish fires. It comes in a sturdy Wooden Box for easy transport and storage. The weight of the agent is 25.3KG and is stored in a Steel Gas Cylinder. The High Light of this system is its use of IG100, a non-polluting Inert Gas Fire Extinguishing System. It can be activated through Automatic or Manual Operation.

Technical Parameters:

Trademark:	RUIGANG
Composition:	Nitrogen
Weight of agent:	25.3KG
Min. extinguishing concentration:	36%
Working Pressure:	200Bar / 20MPa
Max Working Pressure:	23.2MPa
Working temperature:	0°C ~ +50°C
Outside Diameter of Cylinder:	$\Phi 279 \pm 10\text{mm}$
Height of Cylinder:	$1826 \pm 10\text{mm}$

Applications:

Computer rooms

Data centers

Telecommunication facilities

Power plants

Museums

Libraries

Hospitals

Office buildings

The RUIGANG QMD20/90-RG Inert Gas Fire Suppression System is manufactured in Guangzhou, Guangdong, China and is certified by CCC, ISO, CMA, CAL, and CNAS. The minimum order quantity is 1 set and the price is negotiable. The system is packaged in a plywood outer box with bubble bag or paper and can be delivered within 10-15 working days. Payment terms include L/C, D/P, T/T, Western Union, Paypal, and Credit card. The supply ability is 3000 sets per month.

The system has a size of 80L and is shipped by sea. Its minimum working pressure is 18MPa and it can operate in a temperature range of 0°C to +50°C. It is important to note that the RUIGANG QMD20/90-RG Inert Gas Fire Suppression System is a trademark of RUIGANG and is a reliable solution for fire emergencies.

Support and Services:

Our Inert Gas Fire Suppression System product is designed to protect critical assets and sensitive equipment from fire damage. Our technical support team is available 24/7 to assist with any questions or concerns regarding installation, operation, and maintenance of the system. We offer comprehensive services including system design, installation, commissioning, and ongoing maintenance to ensure that your system is always operating at peak performance. Our team of experts will work with you to customize a solution that meets your specific needs and requirements. Contact us to learn more about our Inert Gas Fire Suppression System product and the support and services we offer.

Packing and Shipping:

Product Packaging:

The Inert Gas Fire Suppression System is carefully packed in a sturdy cardboard box.

All components of the system are securely placed in foam compartments to prevent damage during shipping.

The box is labeled with the product name and relevant safety warnings.

Shipping:

The Inert Gas Fire Suppression System is shipped via ground transportation.

Customers can choose to expedite shipping for an additional fee.

A tracking number will be provided to customers once the product has shipped.



Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou