

3kg Fm200 Pneumatic Heat Detection Tube Volume 10L Response Time 3-5 Seconds

Our Product Introduction

for more products please visit us on firefm200.com

Basic Information

- Place of Origin: Guangzhou, Guangdong, China
- Brand Name: RUIGANG
- Certification: CCC/ISO/CMA/CAL/CNAS
- Model Number: TH-Z-Q-6/2.5/170-RG
- Minimum Order Quantity: 1 set
- Price: negotiation
- Packaging Details: Plywood outer box with bubble bag or paper
- Delivery Time: 10~15 working days
- Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card
- Supply Ability: 3000 sets per week



Because we are dedicated,
so we are professional.



Product Specification

- Discharge Mode: Direct Type
- Actuation: Automatic Start
- Volume: 10L
- Response Time: 3-5 Seconds
- Type: Automatic Fire Suppression Tube
- Storage Pressure(20°C): 2.5MPa
- Capacity Of Agent: 3kg Fm200
- Length Of Fire Detector Tube: 20m
- Discharge Mode: Direct
- Highlight: 3kg fm200 pneumatic heat detection tube,
3kg fire detection tube,
3kg pneumatic heat detection tube

Product Description

6kg Fm200 Automatic Fire Suppression Tube 20m Length Fire Detection Tube With 10L Volume

Product Description:

The Automatic Fire Detection Tube Device has a volume of 10L, which makes it ideal for small to medium-sized areas. The device is designed to be easy to install and use, with automatic start actuation that ensures that the device is always ready to use in case of a fire. When it comes to safety, the Automatic Fire Detection Tube Device is second to none. The device has a safety discharge pressure of $5.6\pm0.28\text{MPa}$, which ensures that the device is safe to use and will not cause any harm to people or property. The cylinder of the device is colored in red, which makes it easy to spot in case of an emergency.

The fire detecting tube fire suppression device is an excellent choice for anyone who wants to ensure that their property is protected from fire. With its automatic start actuation, high/low alarm level, and 10L volume, this device is effective in suppressing fires in small to medium-sized areas. The safety discharge pressure of $5.6\pm0.28\text{MPa}$ ensures that the device is safe to use and will not cause any harm to people or property. The red cylinder color makes it easy to spot in case of an emergency.

Features:

Product Name: Fire Detection Tube

Trademark: RUIGANG

Alarm Level: High/Low

Length: 20m

Response Time: 3-5 Seconds

Actuated Temperature ($^{\circ}\text{C}$): $170^{\circ}\text{C}\pm10^{\circ}\text{C}$

The Fire Detection Tube fire suppression system is a reliable and efficient solution for protecting your property from fire. It works by detecting the presence of fire and suppressing it before it can cause damage. This system is often used in conjunction with other fire suppression systems, such as the FM200 Fire Suppression System. The FM200 Fire Detection Tube is a popular choice for many businesses and industries due to its effectiveness and ease of use.

Technical Parameters:

Actuation	Automatic Start
Actuated Temperature ($^{\circ}\text{C}$)	$170^{\circ}\text{C}\pm10^{\circ}\text{C}$
Storage Pressure (20°C)	2.5MPa
Agent	FM200
Type	Automatic Fire Suppression Tube
Safety Discharge Pressure	$5.6\pm0.28\text{MPa}$
Cylinder Color	Red
Trademark	RUIGANG
Length	20m
Response Time	3-5 Seconds

The Fire Detection Tube is an Automatic Fire Suppression Tube that uses FM200 Fire Suppression System. It has a safety discharge pressure of $5.6\pm0.28\text{MPa}$ and a response time of 3-5 seconds. It is a reliable and efficient Fm200 fire trace suppression system.

Applications:

The Fire Detection Tube is a versatile product that can be used in many different situations. It is particularly useful for protecting small enclosed spaces, such as electrical cabinets, server rooms, and control panels. The product is also effective in detecting and extinguishing fires in vehicles, boats, and other mobile equipment.

The Fire Detection Tube is an Automatic FM200 fire extinguishing system. It works by releasing HFC-227ea, a clean and effective fire suppression agent, when the temperature reaches $170^{\circ}\text{C}\pm10^{\circ}\text{C}$. The cylinder color is red, and the storage pressure at 20°C is 2.5MPa. The length of the Fire Detection Tube is 20m, and it is trademarked by RUIGANG.

Overall, the RUIGANG TH-Z-Q-6/2.5/170-RG Fire Detection Tube is an excellent product for anyone who needs an effective and reliable fire detection and suppression system. Whether you need to protect a small enclosed space or a large industrial facility, this product is sure to meet your needs. So why wait? Contact us today to learn more about this amazing product!

Support and Services:

The Fire Detection Tube is a specialized product that requires technical support and services in order to ensure its proper functioning. Our team of experts is available to provide assistance with the installation, maintenance, and troubleshooting of the product. We offer comprehensive technical support services, including:

Product training and education
Installation guidance and support
Product testing and analysis
Remote technical support

In addition to our technical support services, we also offer a range of value-added services to help our customers get the most out of their Fire Detection Tube, including:

Customized product configurations and solutions
Product upgrades and enhancements
Product warranty and repair services

Our goal is to provide our customers with the highest level of support and service, so they can have confidence in the reliability and effectiveness of their Fire Detection Tube.



Because we are dedicated,
so we are professional.



Packing and Shipping:

Product Packaging:

The Fire Detection Tube product will be packed in a sturdy cardboard box that is specially designed to protect the product during transit. The box will be labeled with the product name, quantity, and any other required information for shipping.

Shipping:

The Fire Detection Tube product will be shipped via standard ground shipping. Customers will receive a tracking number once the product has been shipped. The estimated shipping time will be communicated to the customer at the time of purchase. Please note that shipping times may vary based on the destination and any unforeseen delays.



Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou