

6MPa Pressure Restaurant Fire Suppression System With Nitrogen Drive

Basic Information

- Place of Origin: Guangzhou, Guangdong, China
- Brand Name: RUIGANG
- Certification: CCC/ISO/CMA/CAL/CNAS
- Model Number: CMDS22-2-RG
- Minimum Order Quantity: 1 set
- Price: negotiation
- Packaging Details: Plywood outer box with bubble bag or paper
- Delivery Time: 10~15 working days
- Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card
- Supply Ability: 3000 sets per month



Product Specification

- Actuating Temperature: 183°C
- Drive Gas Name: Nitrogen
- Extinguishing Type: Edible Oil Fires
- Weight Of Agent: 14.5kg
- Agent Type: FireFilm-KF
- Storage Pressure: 6 MPa(20°C)
- Warranty: 3 Years
- Nozzle Type: Low Pressure
- Max.working Pressure: 15MPa
- Discharge Time: ≥105s
- Main Control Box Size: 680x600x235(mm)
- Highlight: 6mpa kitchen fire suppression system,
6mpa restaurant fire suppression system,



Product Description

6MPa Pressure Kitchen Fire Suppression System with Nitrogen Drive

Product Description:

Our Kitchen Fire Suppression System is equipped with a high-performance agent that can discharge within 105 seconds. This allows for a quick and effective response to kitchen fires, preventing them from spreading and causing further damage. The agent used in our system is non-toxic, making it safe to use in a food preparation environment.

The Kitchen Fire Suppression System is designed to activate when the temperature reaches 183°C. This ensures that the system is triggered only when necessary, preventing false alarms. The activation temperature is set to trigger when the fire is still manageable, allowing for speedy intervention.

The weight of the agent used in the Kitchen Fire Suppression System is 14.5kg. This ensures that there is enough agent to extinguish the fire effectively and prevent re-ignition.

The activation of the Kitchen Fire Suppression System can be done through automatic or manual operation. This gives you the flexibility to choose the best activation method that suits your needs. The automatic operation system is designed to activate when the temperature reaches the set threshold, while the manual operation system allows for a quick response to a fire by manually activating the system.

The Kitchen Fire Suppression System comes with a nozzle number ranging from 1 to 22. This ensures that the system can be customized to fit any kitchen size and layout. The nozzles are strategically placed to ensure that the agent is effectively distributed, covering all areas of the kitchen.

Don't wait until it's too late. Protect your kitchen, property, and loved ones with our Kitchen Fire Suppression System. Our system is easy to install and maintain, ensuring that you are always protected. Purchase our Kitchen Fire Suppression System today and have peace of mind knowing that you have taken the necessary steps to prevent and extinguish kitchen fires.

Features:

Product Name: Kitchen Fire Suppression System

Agent Type: FireFilm-KF

Drive Gas Name: Nitrogen

Storage Pressure: 6 MPa(20°C)

Warranty: 3 Years

Extinguishing Type: Edible Oil Fires

Technical Parameters:

Kitchen Fire Suppression System	
Nitrogen drive cylinder	4L
Installation Requirements	Professional Installation Required
Volume	9L
Weight of Agent	14.5kg
Drive Gas Name	Nitrogen
Warranty	3 Years
Agent Type	FireFilm-KF
Nozzle Number	1~22
Actuating temperature	183°C
Cylinder Material	Stainless Steel

Applications:

The Kitchen Fire Suppression System is manufactured in Guangzhou, Guangdong, China and is certified by CCC/ISO/CMA/CAL/CNAS. It has a minimum order quantity of 1 set and its price is negotiable. The packaging details include a plywood outer box with bubble bag or paper. The delivery time is 10-15 working days and payment terms include L/C, D/P, T/T, Western Union, Paypal, and Credit card. The supply ability of this kitchen fire suppression device is 3000 sets per month and it comes with a 3-year warranty.

The Kitchen Fire Suppression System is a low-pressure system that features one to 22 nozzles, depending on the size of the kitchen. The agent discharge time is 105 seconds, making it a highly effective fire suppression solution. This system is ideal for use in a range of kitchen applications, including restaurants, hotels, cafes, and other food service establishments.

Agents from FireFilm-KF are used in the Kitchen Fire Suppression System, making it highly effective at extinguishing fires in commercial kitchens. This system is easy to install and can be customized to meet the specific needs of each kitchen. It is an essential safety feature for any commercial kitchen and provides a reliable and effective means of fire protection.

The Kitchen Fire Suppression System is designed for use in a range of kitchen fire suppression scenarios. It is ideal for use in commercial kitchens of all sizes and can be customized to meet the specific needs of each kitchen. Whether you run a small café or a large restaurant, the Kitchen Fire Suppression System is a reliable and effective means of fire protection.



Packing and Shipping:

Product Packaging:

1 Kitchen Fire Suppression System unit

1 User Manual

Shipping:

Shipping method: Standard Ground Shipping

Estimated delivery time: 10-15 business days



Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou