

700L Capacity Mobile Foam Trolley With AFFF/AR Foam Type 8L/S Flow And 25m Hose Length

Our Product Introduction

for more products please visit us on firefm200.com

Basic Information

- Place of Origin: Guangzhou, Guangdong, China
- Brand Name: RUIGANG
- Certification: CCC/ISO/CMA/CAL/CNAS
- Model Number: PY8/700(6%)
- Minimum Order Quantity: 2set
- Price: negotiation
- Packaging Details: Plywood outer box with bubble bag or paper
- Delivery Time: 10~15 working days
- Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card
- Supply Ability: 3000 sets per week



Because we are dedicated,
so we are professional.



Product Specification

- Discharge Distance: $\geq 15\text{m}$
- Mixture Flow: 8L/S
- Working Pressure Range: 0.6~1 MPa
- Tank Capacity: 700L
- Foam Type: AFFF AFFF/AR S S/AR FP/AR G Z
- Hose Length: 25 Meters
- Nozzle Type: Jet/Spray
- Type: Mobile
- Weight Of Agent: 700 Kg
- Color: Red
- Highlight: 700l mobile foam unit, 700l mobile foam trolley, afff mobile foam unit

Product Description

700L Capacity Foam extinguishing installation with AFFF/AR Foam Type 8L/S Flow and 25m Hose Length

Product Description:

The Mobile Foam Unit comes equipped with a 25 meter hose, allowing firefighters to reach fires in hard to reach places. The hose is made of high-quality materials, ensuring that it is durable and long-lasting.

The tank of the Mobile Foam Unit is made of Q235B (Carbon Steel), making it strong and sturdy. The tank has a capacity of 700L, allowing firefighters to tackle fires for an extended period of time without having to refill the tank.

The Mobile Foam Unit is made of steel, ensuring that it is strong and durable. The unit is designed to withstand harsh conditions and can be used in a variety of settings. The unit is easy to operate and can be used by firefighters of all skill levels.

The working pressure range of the Mobile Foam Unit is 0.6~1 (MPa). This range is ideal for extinguishing fires and ensuring that the unit operates at its optimal level. The unit comes equipped with a fixed froth installation, making it easy to apply foam to the fire.

The Mobile Foam Unit is an essential tool for firefighters and emergency responders. It is designed to provide a quick and effective way to extinguish fires in a variety of settings. The unit is easy to operate and can be used by firefighters of all skill levels. The unit is made of high-quality materials, ensuring that it is durable and long-lasting.

Features:

Product Name: Mobile foam unit

Tank Material: Q235B(Carbon Steel)

Weight of Agent: 700 Kg

Foam Type: AFFF,AFFF/AR,S,S/AR,FP/AR ,G,Z

Discharge Time: ≥30min

Material: Steel

Also known as semi-fixed foam unit, mobile foam unit.

Technical Parameters:

Product Attribute	Value
Product Name	Mobile foam unit
Type	Mobile
Foam Type	AFFF,AFFF/AR,S,S/AR,FP/AR ,G,Z
Mixture Flow	8L/S
Discharge Time	≥30min
Working Pressure Range	0.6~1 (MPa)
Tank Material	Q235B(Carbon Steel)
Material	Steel
Mixing Ratio	6%
Weight of Agent	700 Kg
Nozzle Type	Jet/Spray

Applications:

The RUIGANG PY8/700(6%) Mobile foam unit is suitable for a range of occasions and scenarios. For example, it can be used in industrial settings such as oil refineries, chemical plants, and manufacturing facilities to suppress fires in flammable liquids, gases, and solids. It can also be used in commercial settings such as shopping malls, airports, and hotels to protect people, property, and assets.

The RUIGANG PY8/700(6%) Mobile foam unit is a reliable and effective fire suppression solution that can quickly extinguish fires and prevent them from spreading. The unit is made of high-quality steel and can withstand harsh environments. The mixing ratio of the foam agent is 3%, and the tank material is Q235B (Carbon Steel). The unit has a weight of 700 kg and is easy to transport and operate.

The RUIGANG PY8/700(6%) Mobile foam unit has a minimum order quantity of 2 sets and is available for negotiation. The packaging details include a plywood outer box with a bubble bag or paper. The delivery time for the product is around 10-15 working days, and the payment terms include L/C, D/P, T/T, Western Union, Paypal, and Credit card. The supply ability is 3000 sets per week, making it a readily available and accessible solution for fire suppression needs.

Packing and Shipping:

Product Packaging:

1 Mobile Foam Unit

Instruction Manual

Power Cord
Shipping:
Ships within 10-15 business days
International shipping available with additional fees



Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou