

Tank Capacity 400L Portable Foam Unit Discharge Distance 15m

Our Product Introduction

Basic Information

- Place of Origin: Guangzhou, Guangdong, China
- Brand Name: RUIGANG
- Certification: CCC/ISO/CMA/CAL/CNAS
- Model Number: PY8/400(3%)
- Minimum Order Quantity: 2set
- Price: negotiation
- Packaging Details: Plywood outer box with bubble bag or paper
- Delivery Time: 10~15 working days
- Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card
- Supply Ability: 3000 sets per week



Because we are dedicated,
so we are professional.



Product Specification

- Nozzle Type: Jet/Spray
- Mixture Flow: 8L/S
- Discharge Time: ≥ 10 min
- Working Pressure Range: 0.6~1 MPa
- Mixing Ratio: 3%
- Foam Type: AFFF AFFF/AR S S/AR FP/AR G Z
- Weight Of Agent: 400 Kg
- Discharge Distance: ≥ 15 m
- Tank Capacity: 400L
- Highlight: 400l portable foam unit, 400l mobile foam unit, 15m mobile foam unit

Product Description

High-performance mobile foam unit to meet the needs of efficient fire suppression, high quality and good price

Product Description:

The Mobile Foam Unit comes equipped with a 25-meter hose length to allow for maximum reach and flexibility during use. The hose length is the perfect length for use in both indoor and outdoor environments, making it a great option for any situation that requires a foam extinguishing installation.

Our Mobile Foam Unit also features the Jet/Spray nozzle type, allowing for precise application of the foam. This feature is particularly useful when dealing with fires that require a more targeted approach, as it allows for the foam to be applied directly to the source of the fire.

The Mobile Foam Unit is a type of mobile foam extinguishing installation, which means that it can be easily transported to the location of the emergency. This makes it a great option for situations where a fixed froth installation is not available or practical. With its mobility, the Mobile Foam Unit can be used in a variety of locations and situations, including industrial sites, airports, and other outdoor areas.

Another key attribute of our Mobile Foam Unit is its long discharge time of ≥ 10 min. This ensures that you have plenty of time to apply the foam to the source of the fire and extinguish it completely. This feature is particularly important in situations where a fire may be difficult to put out and requires a longer application time.

In summary, our Mobile Foam Unit is a versatile and reliable option for any emergency situation that requires a foam extinguishing installation. With its wide range of foam types, 25-meter hose length, Jet/Spray nozzle type, and long discharge time, you can be sure that the Mobile Foam Unit will meet all of your specific needs and help you to put out fires quickly and efficiently.

Features:

Product Name: Mobile foam unit

Hose Length: 25 Meters

Discharge Distance: ≥ 15 m

Nozzle Type: Jet/Spray

Material: Steel

Discharge Time: ≥ 10 min

Additional keywords: Foam extinguishing installation, Mobile foam fire extinguishing unit, fixed froth installation

Applications:

The RUIGANG PY8/400(3%) Mobile Foam Unit is a versatile product that can be used in a variety of scenarios. It is ideal for extinguishing fires in industrial settings, such as oil refineries, chemical plants, and warehouses. This product is also suitable for use in public buildings, such as schools, hospitals, and shopping malls. The mobile design of the foam unit makes it easy to move from location to location, making it an ideal choice for emergency responders.

The RUIGANG PY8/400(3%) Mobile Foam Unit is equipped with a Jet/Spray nozzle, allowing users to adjust the flow of foam to meet the needs of their specific application. The 400L tank capacity and mixture flow rate of 8L/S ensure that the foam unit is capable of extinguishing large fires quickly and efficiently. The discharge time of ≥ 10 min provides ample time for the user to control the fire and prevent it from spreading.

Customers can order a minimum of 2 sets of the RUIGANG PY8/400(3%) Mobile Foam Unit, and the price is negotiable. The product is packaged in a plywood outer box with bubble bag or paper to ensure it arrives in optimal condition. Delivery time is typically 10~15 working days, and payment terms include L/C, D/P, T/T, Western Union, Paypal, and credit card. The supply ability of the product is 3000 sets per week.

In conclusion, the RUIGANG PY8/400(3%) Mobile Foam Unit is an efficient and versatile fire extinguishing installation that is ideal for use in a variety of scenarios. Its mobile design, adjustable nozzle, and large tank capacity make it an ideal choice for emergency responders and industrial settings.

Customization:

Our product is manufactured in Guangzhou, Guangdong, China with certifications including CCC, ISO, CMA, CAL, and CNAS. The minimum order quantity is 2 sets, and pricing is available through negotiation. Packaging details include a plywood outer box with bubble bag or paper for safe transport.

Delivery time for our mobile foam unit is 10-15 working days, and payment terms accepted include L/C, D/P, T/T, Western Union, Paypal, and Credit Card. With a supply ability of 3000 sets per week, we are confident in our ability to meet your needs.

Choose from foam types including AFFF, AFFF/AR, S, S/AR, FP/AR, G, and Z. Nozzle types include Jet/Spray, and the unit itself is mobile for easy maneuverability. This product is perfect for those in need of a customizable, reliable foam fire extinguishing unit.

Don't settle for a fixed froth installation - choose the RUIGANG Mobile Foam Fire Extinguishing Unit for all your fire suppression needs.

Packing and Shipping:

Product Packaging:

Mobile foam unit

Instruction manual

2 foam solution tanks

Wheels and handle for mobility

Protective foam padding

Shipping Information:

Ships within 10-15 business days
Shipping cost: calculated at checkout



Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou