

Portable Firefighting Mobile Foam Unit 400Kg Agent Weight 0.6-1MPa Working Pressure

Our Product Introduction

for more products please visit us on firefm200.com

Basic Information

- Place of Origin: Guangzhou, Guangdong, China
- Brand Name: RUIGANG
- Certification: CCC/ISO/CMA/CAL/CNAS
- Model Number: PY8/400(6%)
- Minimum Order Quantity: 2set
- Price: negotiation
- Packaging Details: Plywood outer box with bubble bag or paper
- Delivery Time: 10~15 working days
- Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card
- Supply Ability: 3000 sets per week



Because we are dedicated,
so we are professional.



Product Specification

- Discharge Time: ≥ 25
- Tank Capacity: 400L
- Weight Of Agent: 400 Kg
- Hose Length: 25 Meters
- Working Pressure Range: 0.6~1 MPa
- Tank Material: Q235B Carbon Steel
- Foam Type: AFFF AFFF/AR S S/AR FP/AR G Z
- Type: Mobile
- Mixing Ratio: 6%
- Highlight: mobile foam unit 400kg,
400kg mobile foam system,
0.6-1mpa mobile foam unit

Product Description

400L Mobile Foam Unit 400 Kg Agent Weight 25M Hose Length 0.6-1MPa Working Pressure Portable Firefighting

Product Description:

With a discharge distance of at least 15 meters, the Mobile Foam Unit can reach flames that may be out of reach for other extinguishers. This makes it ideal for large-scale fires that require a more powerful solution. The unit's working pressure range of 0.6~1 (MPa) allows for a consistent and reliable flow of foam solution, ensuring that flames are extinguished quickly and efficiently.

In addition to its impressive range and pressure, the Mobile Foam Unit boasts a discharge time of at least 10 minutes. This extended discharge time is critical in ensuring that the fire is fully extinguished, rather than simply being suppressed and potentially reigniting later. Overall, the Mobile Foam Unit is an excellent choice for anyone in need of a reliable and efficient foam extinguishing installation. Its large tank capacity, proper mixing ratio, long discharge distance, consistent working pressure, and extended discharge time make it a standout product in the market. Invest in the Mobile Foam Unit today for peace of mind and effective fire suppression.

Features:

Product Name: Mobile foam unit

Discharge Distance: $\geq 15\text{m}$

Mixture Flow: 8L/S

Working Pressure Range: 0.6~1 (MPa)

Mixing Ratio: 6%

Hose Length: 25 Meters

Keywords: Fire extinguishing installation, Fire extinguishing installation, Foam extinguishing installation

Applications:

The RUIGANG Mobile foam unit is certified by CCC/ISO/CMA/CAL/CNAS, ensuring that it meets all the necessary quality and safety standards. This product has a minimum order quantity of 2 sets and a supply ability of 3000 sets per week, making it ideal for large scale applications.

The nozzle type of the RUIGANG Mobile foam unit is both jet and spray, which makes it versatile in its application. With a mixing ratio of 6%, this mobile foam unit can be used to extinguish a wide variety of fire types, including AFFF, AFFF/AR, S, S/AR, FP/AR, G, and Z.

The RUIGANG Mobile foam unit can be used in a variety of scenarios, including oil fields, chemical plants, ships, airports, and other industrial settings. This product is designed to quickly and effectively extinguish fires, making it an essential tool for any fire safety plan.

The packaging of the RUIGANG Mobile foam unit consists of a plywood outer box with bubble bag or paper, ensuring that the product is well-protected during transportation. The delivery time for this product is 10-15 working days, and payment can be made through L/C, D/P, T/T, Western Union, Paypal, or credit card.

In conclusion, the RUIGANG Mobile foam unit is a high-quality fire extinguishing installation that is perfect for a wide variety of application occasions and scenarios. Its durable construction, versatile nozzle type, and ability to extinguish multiple types of fires make it an essential tool for any fire safety plan.

Customization:

Introducing our customizable mobile foam unit product from RUIGANG. This fire extinguishing installation comes with a model number of PY8/400(6%) and is manufactured in Guangzhou, Guangdong, China. It is certified by CCC/ISO/CMA/CAL/CNAS and has a minimum order quantity of 2 sets with a negotiable price.

The packaging details include a plywood outer box with either a bubble bag or paper. The delivery time for this product is approximately 10 to 15 working days, and we accept various payment terms such as L/C, D/P, T/T, Western Union, Paypal, and Credit Card. The supply ability for this product is 3000 sets per week.

Some customizable attributes for this mobile foam unit include a hose length of 25 meters, and a choice of foam type between AFFF, AFFF/AR, S, S/AR, FP/AR, G, and Z. The mixture flow for this unit is 8L/S, and it has a tank capacity of 400L with a weight of agent at 400kg.

For those interested in fixed froth installation, our mobile foam unit is the perfect solution for your fire extinguishing needs.

Packing and Shipping:

Product Packaging:

Mobile foam unit

Instruction manual

Shipping:

Shipped via standard ground shipping

Expected delivery within 5-7 business days

Shipping cost calculated at checkout

Tracking information provided via email



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou