

300L Carbon Steel Tank Mobile Foam Fire Extinguishing Unit With Jet Spray Nozzles

Our Product Introduction

for more products please visit us on firefm200.com

Basic Information

- Place of Origin: Guangzhou, Guangdong, China
- Brand Name: RUIGANG
- Certification: CCC/ISO/CMA/CAL/CNAS
- Model Number: PY8/300(3%)
- Minimum Order Quantity: 2set
- Price: negotiation
- Packaging Details: Plywood outer box with bubble bag or paper
- Delivery Time: 10~15 working days
- Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card
- Supply Ability: 3000 sets per week



Because we are dedicated,
so we are professional.



Product Specification

- Mixture Flow: 8L/S
- Tank Capacity: 300L
- Discharge Distance: $\geq 15\text{m}$
- Type: Mobile
- Nozzle Type: Jet/Spray
- Working Pressure Range: 0.6~1 MPa
- Tank Material: Q235B Carbon Steel
- Discharge Time: $\geq 10\text{min}$
- Weight Of Agent: 300kg
- Hose Length: 25m
- Highlight: 300L Carbon Steel Tank mobile foam tank,
mobile foam tank With Jet Spray Nozzles,
300L Mobile Foam Fire Extinguishing Unit

Product Description

300L Carbon Steel Tank Mobile foam fire extinguishing unit With Jet Spray Nozzles

Product Description:

The Mobile Foam Unit is designed with a fixed froth installation, ensuring consistent and reliable foam production. The unit features a discharge distance of at least 15m, making it ideal for use in large spaces. With a mixture flow of 8L/S and a mixing ratio of 3%, the Mobile Foam Unit is capable of quickly and effectively suppressing fires.

Whether you are dealing with a small fire or a large-scale emergency, the Mobile Foam Unit is the perfect tool for the job. Its compact size and maneuverability make it easy to transport and use in a variety of settings.

When it comes to fire suppression and control, you need a product that you can trust. The Mobile Foam Unit is built to perform, with a fixed froth installation that ensures consistent and reliable foam production. With a tank capacity of 200L and a discharge distance of at least 15m, this unit is capable of tackling even the most challenging fires.

Invest in the Mobile Foam Unit today and experience the peace of mind that comes with knowing you have the best fire suppression and control tool at your fingertips.

Features:

Product Name: Mobile foam unit

Nozzle Type: Jet/Spray

Discharge Distance: ≥15m

Hose Length: 25 Meters

Tank Material: Q235B(Carbon Steel)

Discharge Time: ≥10min

The Mobile foam unit is a fire extinguishing installation that is highly effective in putting out fires. It is a mobile froth apparatus that can discharge foam at a distance of at least 15 meters. The hose length of 25 meters allows for easy maneuverability and coverage. The tank material used is Q235B (Carbon Steel) which ensures durability and longevity of the product. With a discharge time of at least 10 minutes, the Mobile foam unit is a reliable and efficient tool for fire extinguishing.

Applications:

The Mobile foam fire extinguishing unit has a minimum order quantity of 2 sets and its price is negotiable. The product is well-packaged in a plywood outer box with a bubble bag or paper. Delivery time takes between 10 to 15 working days. Payment can be made through L/C, D/P, T/T, Western Union, Paypal, and Credit card. RUIGANG's supply ability for the Mobile foam unit is 3000 sets per week.

The Mobile foam unit has a discharge distance of at least 15m and has a tank capacity of 300L. The product is made of high-quality steel material and has a discharge time of at least 10 minutes. These attributes make the Mobile foam unit a reliable choice for dealing with fires, especially in industries such as oil and gas, petrochemical, and marine.

The Mobile foam unit can be used in various application occasions and scenarios such as:

Oil refineries and chemical plants

Offshore drilling rigs and ships

Aircraft hangars and airports

Warehouses and storage facilities

Power plants and substations

Industrial and manufacturing facilities

With its mobility and ease of use, the Mobile foam unit can be quickly deployed to any location where there is a potential fire hazard. It is also suitable for use in situations where water or other extinguishing agents may not be effective, such as fires involving flammable liquids or gases. The product's high-quality construction and reliable performance make it an essential tool for fire safety professionals and emergency responders.

Customization:

Model number PY8/300(3%) ensures that you get the best performance. Our Mobile foam units are manufactured in Guangzhou, Guangdong, China and have the necessary certifications including CCC/ISO/CMA/CAL/CNAS.

The minimum order quantity is 2 sets and the pricing is negotiable. The packaging details include plywood outer boxes with bubble bags or paper for extra protection during shipping.

We have a supply ability of 3000 sets per week and a delivery time of 10-15 working days. Payment terms include L/C, D/P, T/T, Western Union, Paypal, and Credit card.

The Mobile Foam Unit is made of high-quality steel and has a mixture flow of 8L/S. The discharge time is ≥10min, ensuring ample time for fire suppression. Additionally, the hose length is 25 meters, allowing for versatile use.

Packing and Shipping:

Product Packaging:

1 Mobile Foam Unit

Instruction Manual

Battery Charger

Shipping:

Land transport



Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou