

Steel Mobile Foam Unit Foam Extinguishing Installation With 300L Capacity And 3% Mixing Ratio

Our Product Introduction

for more products please visit us on firefm200.com

Basic Information

- Place of Origin: Guangzhou, Guangdong, China
- Brand Name: RUIGANG
- Certification: CCC/ISO/CMA/CAL/CNAS
- Model Number: PY8/300(6%)
- Minimum Order Quantity: 2set
- Price: negotiation
- Packaging Details: Plywood outer box with bubble bag or paper
- Delivery Time: 10~15 working days
- Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card
- Supply Ability: 3000 sets per week



Because we are dedicated,
so we are professional.



Product Specification

- Discharge Time: ≥ 10 min
- Tank Material: Q235B Carbon Steel
- Mixing Ratio: 6%
- Material: Steel
- Hose Length: 25 Meters
- Tank Capacity: 300L
- Nozzle Type: Jet/Spray
- Weight Of Agent: 300 Kg
- Spray Distance: ≥ 10 m
- Highlight: steel mobile foam unit,
steel mobile foam system, 300l mobile foam unit

Product Description

Steel Mobile Foam Unit Foam Extinguishing Installation with 300L Capacity and 3% Mixing Ratio

Product Description:

The Mobile Foam Fire Extinguishing Unit has a discharge distance of at least 15 meters, making it an effective tool for extinguishing fires from a safe distance. The unit is capable of producing different types of foam, including AFFF, AFFF/AR, S, S/AR, FP/AR, G, and Z foams, making it a versatile tool for firefighting professionals.

The tank material of the Mobile Foam Fire Extinguishing Unit is made of Q235B carbon steel, ensuring its durability and ability to withstand harsh conditions. This fixed froth installation is designed to be easy to use, even for those without extensive firefighting training. Simply connect the unit to a water source and it is ready to use.

Overall, the Mobile Foam Fire Extinguishing Unit is an essential tool for any organization looking to improve their fire safety measures. Its mobility, versatility, and ease of use make it a valuable asset in any firefighting situation. Don't wait until it's too late, invest in the Mobile Foam Fire Extinguishing Unit today.

Features:

Product Features:

Product Name: Mobile foam unit

Mixture Flow: 8L/S

Discharge Time: ≥10min

Working Pressure Range: 0.6~1 (MPa)

Type: Mobile

Hose Length: 25 Meters

This product is a type of foam extinguishing installation, commonly known as a Mobile foam unit. It has a mixture flow of 8L/S and a discharge time of at least 10 minutes. The working pressure range is between 0.6 and 1 MPa. It is designed to be mobile, allowing for easy transportation and deployment. It also comes with a hose length of 25 meters, providing ample reach for extinguishing fires.

Applications:

The mobile foam unit is ideal for situations where a fixed froth installation is not possible or practical. It can be easily transported to different locations and used to extinguish fires in a variety of scenarios. For example, the mobile foam unit is perfect for use in warehouses, factories, airports, and other large-scale facilities. It can also be used in outdoor settings, such as oil rigs, shipyards, and construction sites.

The RUIGANG mobile foam unit is certified by CCC, ISO, CMA, CAL, and CNAS, ensuring that it meets the highest quality standards. It has a minimum order quantity of 2 sets and is available at a negotiated price. The packaging details include a plywood outer box with a bubble bag or paper, and the delivery time is 10-15 working days.

The mobile foam unit has a discharge time of at least 10 minutes and a hose length of 25 meters. It operates within a working pressure range of 0.6~1 (MPa) and has a mixing ratio of 3%. This makes it ideal for use in a range of fire suppression scenarios.

Whether you need a foam extinguishing installation for a large-scale facility or a mobile foam unit for outdoor use, the RUIGANG PY8/300(6%) is an excellent choice. With a supply ability of 3000 sets per week, RUIGANG is committed to providing customers with high-quality firefighting equipment that meets their needs.

Customization:

Brand Name: RUIGANG

Model Number: PY8/300(6%)

Place of Origin: Guangzhou, Guangdong, China

Certification: CCC/ISO/CMA/CAL/CNAS

Minimum Order Quantity: 2 sets

Price: Negotiation

Packaging Details: Plywood outer box with bubble bag or paper

Delivery Time: 10~15 working days

Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card

Supply Ability: 3000 sets per week

Weight of Agent: 300 Kg

Tank Capacity: 300L

Hose Length: 25 Meters

Nozzle Type: Jet/Spray

Discharge Distance: ≥15m

Equip yourself with the best Mobile Froth Apparatus in the market with its customizable features to suit your specific needs. Let us help you safeguard your property and people with the reliable RUIGANG Mobile Foam Unit.

Packing and Shipping:

Product Packaging:

Mobile foam unit

Instruction manual

Power cord

Extra foam concentrate

Set of keys

Shipping:

Ships within 10-15 business days

International shipping available at an additional cost

Tracking information provided



Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou