

## Capacity 200 Liter Mobile Foam System 8L/S Flow Rate for AFFF S Foam Types

Our Product Introduction

for more products please visit us on [firefm200.com](http://firefm200.com)

### Basic Information

- Place of Origin: Guangzhou, Guangdong, China
- Brand Name: RUIGANG
- Certification: CCC/ISO/CMA/CAL/CNAS
- Model Number: PY8/200(6%)
- Minimum Order Quantity: 2set
- Price: negotiation
- Packaging Details: Plywood outer box with bubble bag or paper
- Delivery Time: 10~15 working days
- Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card
- Supply Ability: 3000 sets per week



### Product Specification

- Type: Mobile
- Mixture Flow: 8L/S
- Foam Type: AFFF AFFF/AR S S/AR FP/AR G Z
- Discharge Distance:  $\geq 15\text{m}$
- Weight Of Agent: 200 Kg
- Hose Length: 25 Meters
- Tank Material: Q235B Carbon Steel
- Tank Capacity: 200L
- Highlight: mobile foam system 8l/s,  
200 liter mobile foam system,  
8l/s mobile foam unit

## Product Description

Capacity 200L Mobile Foam System 8L/S Flow Rate for AFFF S Foam Types

### Product Description:

The Mobile Foam Unit is made of high-quality steel, ensuring durability and longevity even in the most challenging environments. Its tank capacity of 200L is perfect for small to medium-sized facilities, allowing for longer operational time without the need for frequent refills. The tank material used in this product is Q235B (Carbon Steel), which is known for its strength and resistance to corrosion.

The hose length of 25 meters provides ample reach and flexibility, allowing for easy maneuvering and application of foam to the affected areas. This product is also equipped with various foam types to choose from, including AFFF, AFFF/AR, S, S/AR, FP/AR, G, and Z, ensuring that you have the right foam type for any type of fire hazard that may occur.

The Mobile Foam Unit is a fixed froth installation that is easy to operate and requires minimal maintenance. Its compact design allows for easy storage and transportation, making it an ideal choice for industries that require quick and efficient foam extinguishing installations. Overall, the Mobile Foam Unit is an excellent investment for any company or facility that prioritizes safety and protection. With its high-quality components, reliable performance, and easy operation, you can be sure that your facility and personnel are well-protected in case of any fire emergencies.

### Features:

Product Name: Mobile foam unit

Material: Steel

Mixing Ratio: 6%

Tank Material: Q235B(Carbon Steel)

Hose Length: 25 Meters

Working Pressure Range: 0.6~1 (MPa)

Other names for this product include: mobile froth apparatus, Foam extinguishing installation, and fixed froth installation.



### Applications:

The RUIGANG mobile foam unit PY8/200(6%) is a highly efficient and reliable foam extinguishing installation that is perfect for a wide range of application occasions and scenarios. With its outstanding features and certifications such as CCC/ISO/CMA/CAL/CNAS, this product is an ideal choice for customers who demand high quality and reliability.

The mobile froth apparatus is suitable for various industries such as oil, petrochemical, chemical, power, transportation, and other industrial plants. It is widely used in fire extinguishing and fire fighting for liquid fuel fires, chemical fires, and solid combustible fires. The nozzle type of this product is Jet/Spray, which can provide a powerful and accurate flow for effective fire extinguishing.

This foam extinguishing installation has a discharge time of  $\geq 10$ min and can provide a mixture flow of 8L/S. The foam type options include AFFF, AFFF/AR, S, S/AR, FP/AR, G, and Z, which can meet different fire extinguishing requirements. The tank capacity of 200L is sufficient for most fire extinguishing scenarios, and the foam mixture can be quickly and easily refilled.

RUIGANG mobile foam unit PY8/200(6%) is designed for easy mobility and deployment. It is equipped with a sturdy frame and wheels, which makes it easy to move around and operate. The plywood outer box with bubble bag or paper packaging ensures that the product is well protected during transportation.

The delivery time of this product is 10~15 working days, and the minimum order quantity is 2 sets. The price is negotiable, and the payment terms include L/C, D/P, T/T, Western Union, Paypal, and Credit card. With a supply ability of 3000 sets per week, customers can be assured of timely delivery and availability of this product.

In summary, the RUIGANG mobile foam unit PY8/200(6%) is an excellent foam extinguishing installation that is suitable for a wide range of application occasions and scenarios. With its high quality, reliability, and mobility, it is an ideal choice for customers who demand effective and efficient fire extinguishing solutions.

### Packing and Shipping:

Product Packaging:

Mobile foam unit

Instruction manual

Accessories (hoses, nozzles, etc.)

Shipping:

Ships within 10-15 business days

International shipping available

Shipping rates calculated at checkout



**Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.**



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou