

## 2.5MPa Novec 1230 Clean Gas Fire Suppression System Cylinder Capacity 40L

Our Product Introduction

for more products please visit us on [firefm200.com](http://firefm200.com)

### Basic Information

- Place of Origin: Guangzhou, Guangdong, China
- Brand Name: RUIGANG
- Certification: CE/CCC/ISO/CMA/CAL/CNAS
- Model Number: YF40/2.5N-RG
- Minimum Order Quantity: 1 set
- Price: negotiation
- Packaging Details: Plywood outer box with bubble bag or paper
- Delivery Time: 5~10 working days
- Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card
- Supply Ability: 3000 sets per week



### Product Specification

- Agent Type: Clean Agent
- Feature: Clean Gas And Environmental Friendly
- Activation Method: Electric/Manual
- Spraying Time: ≤10s
- Discharge Time: 10 Seconds
- Nominal Pressure: 2.5MPa
- Color: Yellow
- Cylinder Capacity: 40L
- Size(mm): 500\*450\*1450
- Working Temperature: -10°C~50°C
- Storage Pressure: 2.5MPa
- Highlight: 2.5mpa novtec 1230,  
2.5mpa clean gas fire suppression system,

## Product Description

### Clean and Environmentally Friendly Clean Gas Fire Suppression 40L Cylinder for Quick Activation

#### Product Description:

The NOVEC 1230 Fire Suppression System has a spraying time of less than 10 seconds, which ensures that fires are put out quickly and efficiently. It also has a discharge time of 10 seconds, which means that the fire suppression agent is released into the protected area in a controlled and measured manner. This avoids the risk of damaging the protected assets due to excessive pressure or the sudden release of the agent.

The NOVEC 1230 Fire Suppression System is designed to protect enclosed areas with a proportion of up to 500m<sup>2</sup> or a volume of up to 1600m<sup>3</sup>. This makes it ideal for use in small to medium-sized enclosed spaces where valuable assets are stored. The system can be activated either electrically or manually, depending on the specific requirements of the protected area.

The clean agent used in the NOVEC 1230 Fire Suppression System is Perfluorohexone (FK-5-1-12). This agent is a highly effective fire suppressant that is non-toxic, non-conductive, and does not leave any residue after use.

In summary, the NOVEC 1230 Fire Suppression System is an advanced automatic fire extinguishing system that is designed to protect enclosed areas with valuable assets. It has a spraying time of less than 10 seconds, a discharge time of 10 seconds, and can protect areas with a proportion of up to 500m<sup>2</sup> or a volume of up to 1600m<sup>3</sup>. It can be activated electrically or manually, and uses Perfluorohexone (FK-5-1-12) as its clean agent, which is safe, non-toxic, non-conductive, and leaves no residue after use.

#### Features:

Product Name: Novec 1230 Fire Suppression System

Company Type: Manufacturer Over 20-years

Agent Type: Clean Agent (Perfluorohexone)

Protected Zone Range: Proportion: ≤500m<sup>2</sup> Volume: ≤1600m<sup>3</sup>

Feature: Clean Gas And Environmental Friendly

Spraying Time: ≤10s

#### Technical Parameters:

Product Attribute	Value
Company Type	Manufacturer Over 20-years
Discharge Time	10 Seconds
Working Temperature	-10°C 50°C
Activation Method	Electric/Manual
Cylinder Capacity	40L
Color	Yellow
Nominal Pressure	2.5MPa
Maximum protection volume	64m <sup>3</sup>
Cylinder Volume	40L
Size(mm)	500*450*1450

#### Applications:

This FK-5-1-12 automatic fire extinguishing equipment is certified by CE, CCC, ISO, CMA, CAL, and CNAS, ensuring its reliability and effectiveness. With a minimum order quantity of 1 set and a negotiation-based price, the RUIGANG YF40/2.5N-RG is an affordable solution for companies of all sizes.

The cylinder capacity of 40L and nominal pressure of 2.5MPa allow for a discharge time of 10 seconds, providing quick and efficient fire suppression in the event of an emergency. The protected zone range is proportionate to ≤500m<sup>2</sup> or volume of ≤1600m<sup>3</sup>, with a maximum protection capacity of 64m<sup>3</sup>.

The RUIGANG YF40/2.5N-RG is supplied in a plywood outer box with a bubble bag or paper packaging, ensuring safe transportation and delivery. With a supply ability of 3000 sets per week, customers can rely on a steady and consistent supply of this fire suppression system.

Payment terms for the RUIGANG YF40/2.5N-RG include L/C, D/P, T/T, Western Union, Paypal, and credit card, providing flexibility for customers to choose the option that best suits their needs. With its excellent quality and effectiveness, this cabinet fire extinguishing system is a reliable choice for protecting valuable assets.

#### Customization:

Customize your RUIGANG NOVEC 1230 Fire Suppression System with our product customization services. Our FK-5-1-12 automatic fire extinguishing equipment is designed to protect your valuable assets in case of fire. The Perfluorohexone cabinet fire extinguishing system is perfect for use in cabinets and other small spaces. The cabinet automatic fire extinguishing system is a reliable choice for protecting

your equipment from the devastating effects of fire.  
Brand Name: RUIGANG  
Model Number: YF40/2.5N-RG  
Place of Origin: Guangzhou, Guangdong, China  
Certification: CE/CCC/ISO/CMA/CAL/CNAS  
Minimum Order Quantity: 1 set  
Price: Negotiation  
Packaging Details: Plywood outer box with bubble bag or paper  
Delivery Time: 5~10 working days  
Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card  
Supply Ability: 3000 sets per week  
Activation Method: Electric/Manual  
Company Type: Manufacturer Over 20-years  
Color: Yellow  
Discharge Time: 10 Seconds  
Nominal Pressure: 2.5MPa

### Support and Services:

The NOVEC 1230 Fire Suppression System is a clean agent fire protection solution that is safe for use in occupied spaces. It is designed to quickly extinguish fires and minimize damage to property and equipment. This product is backed by comprehensive technical support and services, including:

System design and engineering

Installation guidance and technical support

Training and education

Emergency service and support

Our team of experts is dedicated to ensuring that your NOVEC 1230 Fire Suppression System is installed and maintained properly, and that you receive the highest level of support throughout the life of your system.

### Packing and Shipping:

Product Packaging:

The NOVEC 1230 Fire Suppression System product comes in a sturdy cardboard box.

The product is securely packed with foam padding to prevent damage during transit.

The box contains the NOVEC 1230 fire suppression system, installation instructions, and a user manual.

Shipping:

The NOVEC 1230 Fire Suppression System product is shipped via ground shipping.

Shipping times vary depending on the shipping destination.

Customers will receive a tracking number once the product has been shipped.



**Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.**



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou