

## 150L Clean Gas NOVEC 1230 Fire Suppression System 10 Seconds Discharge Time 240m3 Protection

Our Product Introduction

for more products please visit us on [firefm200.com](http://firefm200.com)

### Basic Information

- Place of Origin: Guangzhou, Guangdong, China
- Brand Name: RUIGANG
- Certification: CE/CCC/ISO/CMA/CAL/CNAS
- Model Number: YF150/2.5N-RG
- Minimum Order Quantity: 1 set
- Price: negotiation
- Packaging Details: Plywood outer box with bubble bag or paper
- Delivery Time: 5~10 working days
- Payment Terms: L/C, T/T
- Supply Ability: 3000 sets per week



### Product Specification

- Maximum Protection Capacity: 240m<sup>3</sup>
- Color: Yellow
- Maximum Filling Weight: 213kg
- Working Temperature: -10°C 50°C
- Company Type: Manufacturer Over 20-years
- Cylinder Volume: 150L
- Feature: Clean Gas And Environmental Friendly
- Discharge Time: 10 Seconds
- Working Pressure: 2.5MPa
- Size(mm): 500\*450\*1850
- Highlight: 150l novac gas, 150l gas novac 1230, 240m3 novac gas

## Product Description

### Yellow 150L Clean Gas NOVEC 1230 Fire Suppression System 10 Seconds Discharge Time 240m<sup>3</sup> Protection

#### Product Description:

The NOVEC 1230 Fire Suppression System has a nominal pressure of 2.5MPa, ensuring that the agent is delivered quickly and efficiently to the protected area. The cylinder material is made of steel, providing durability and reliability for long-term use. The system also has a discharge time of 10 seconds, which is a crucial feature in fire suppression systems as it allows for quick and effective extinguishing of the fire.

This fire suppression system is manufactured by a company that has over 20 years of experience in the industry, ensuring that customers receive high-quality and reliable products. The NOVEC 1230 Fire Suppression System is designed to protect critical assets, including data centers, telecommunications facilities, and other sensitive equipment.

The NOVEC 1230 cabinet automatic fire extinguishing equipment is easy to install and operate and is designed to protect small enclosures such as electrical cabinets, switchgear, and control panels. The system provides 24/7 protection and can detect and extinguish a fire without human intervention, ensuring that critical assets are protected at all times.

In summary, the NOVEC 1230 Fire Suppression System is an FK-5-1-12 Automatic fire extinguishing system that uses a clean agent called Perfluorohexone (C6F12O) or Novec 1230. It has a nominal pressure of 2.5MPa, a steel cylinder material, and a discharge time of 10 seconds. The system is manufactured by a company with over 20 years of experience in the industry and is designed to protect critical assets such as data centers and telecommunications facilities. The NOVEC 1230 cabinet automatic fire extinguishing equipment is easy to install and operate and provides 24/7 protection for small enclosures such as electrical cabinets, switchgear, and control panels.

#### Features:

Product Name: NOVEC 1230 Fire Suppression System

Working Temperature: -10°C 50°C

Cylinder Capacity: 150L

Maximum filling weight: 213kg

Color: Yellow

Maximum protection capacity: 240m<sup>3</sup>

The NOVEC 1230 Fire Suppression System is a Perfluorohexone cabinet fire extinguishing system that uses Perfluorohexone as the extinguishing agent.

#### Technical Parameters:

Maximum protection capacity	240m <sup>3</sup>
Agent Type	Clean Agent
Feature	Clean Gas And Environmental Friendly
Spraying Time	≤10s
Color	Yellow
Activation Method	Electric/Manual
Maximum filling weight	213kg
Working Temperature	-10°C 50°C
Protected Zone Range	Proportion: ≤500m <sup>2</sup> Volume: ≤1600m <sup>3</sup>
Nominal Pressure	2.5MPa

#### Applications:

The packaging details for this Perfluorohexone cabinet fire extinguishing system include a plywood outer box with bubble bag or paper for safe transportation. The delivery time for this product is 5-10 working days, and payment terms include L/C, T/T. The supply ability for this product is 3000 sets per week.

The RUIGANG YF150/2.5N-RG has a working temperature range of -10°C 50°C, making it suitable for a wide range of environments.

The activation method for this system can be either electric or manual, depending on the user's preference. The agent type for this system is clean agent, which means it is safe for use in areas with sensitive equipment or materials.

This Perfluorohexone cabinet fire extinguishing system has a size of 500\*450\*1850mm, and is able to protect a zone range of proportion: ≤500m<sup>2</sup> and volume: ≤1600m<sup>3</sup>. This makes it ideal for use in areas such as computer rooms, archives, data centers, and other facilities where sensitive equipment and materials must be protected from fire damage.

Overall, the RUIGANG YF150/2.5N-RG is a high-quality Perfluorohexone automatic fire extinguishing system that is suitable for a wide range of applications. Whether you need to protect a small server room or a large data center, this Novec 1230 cabinet automatic fire extinguishing equipment is an excellent choice that can help keep your equipment and materials safe from fire damage.

#### Customization:

RUIGANG offers product customization services for the YF150/2.5N-RG Novec 1230 cabinet automatic fire extinguishing equipment. Our

product is made in Guangzhou, Guangdong, China and is certified with CE/CCC/ISO/CMA/CAL/CNAS. The minimum order quantity is 1 set and the price is negotiable.

The packaging details include plywood outer box with bubble bag or paper. The delivery time is 5~10 working days and we accept payment terms such as L/C, T/T. Our supply ability is 3000 sets per week.

The nominal pressure is 2.5MPa and the agent type is clean agent. Our maximum protection capacity is 64m³ and the size of our product is 500\*450\*1850mm. The color of the product is yellow.

Our YF150/2.5N-RG cabinet automatic fire extinguishing system is a Perfluorohexone fire extinguishing system. Contact us for more information on our product customization services.

### Support and Services:

The NOVEC 1230 Fire Suppression System product offers comprehensive technical support and services to ensure optimal performance and reliability. Our team of experienced professionals provides expert installation, maintenance, and repair services to ensure that your system is always up and running when you need it most. We also offer ongoing training and support to help you get the most out of your NOVEC 1230 Fire Suppression System, including detailed product specifications, installation guides, and troubleshooting tips. Whether you need assistance with installation, maintenance, or repair, our team is here to help you every step of the way.

### Packing and Shipping:

Product Packaging:

The NOVEC 1230 Fire Suppression System is packaged in a sturdy cardboard box to ensure safe delivery. Inside the box, the system components are securely packed with foam and other protective materials to prevent any damage during transportation.

Shipping:

Our shipping process is efficient and reliable. We use trusted carriers to ensure your NOVEC 1230 Fire Suppression System is delivered to your doorstep in a timely and safe manner. Shipping fees may vary depending on your location and the size of your order.



**Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.**



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou