

# 10s Novec 1230 Clean Agent Fire Suppression System Max Protection Volume 192m3

# **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:

• Price:

- Model Number:
- Minimum Order Quantity:
  - negotiation
- Packaging Details: Plywood outer box with bubble bag or paper

RUIGANG

1 set

YF120/2.5N-RG

Guangzhou, Guangdong, China

CE/CCC/ISO/CMA/CAL/CNAS

- Delivery Time: 5~10 working days
- Payment Terms: L/C, T/T
- Supply Ability: 3000 sets per week



🛃 广州瑞港消防设备有限公司

# **Product Specification**

- Working Temperature: -10°C 50°C
- Maximum Filling Weight:170.4kg
- Spraying Time: ≤10s
- Color: Yellow
- Discharge Time: 10 Seconds
- Agent Type: Clean Agent
- Company Type: Manufacturer Over 20-years
- Nominal Pressure: 2.5MPa
- Maximum Protection 192m<sup>3</sup>
  Volume:
- Working Temperature: -10°C~50°C
- Size(mm): 500\*450\*1900
- Highlight: 10s novec 1230 clean agent fire suppression



Yellow Clean Agent Fire Suppression System with 170.4kg Filling Capacity and 2.5MPa Nominal Pressure

#### **Product Description:**

The system comes in a bright yellow color, making it easy to identify in case of an emergency. It can be activated either by an electric or manual method, giving users the flexibility to choose the best option depending on their needs.

One of the key features of the NOVEC 1230 Fire Suppression System is its maximum protection capacity of m<sup>3</sup>. This means that it can cover a large area, making it ideal for use in commercial, industrial, and residential settings.

The system uses the FK-5-1-12 agent, which is a clean gas and environmentally friendly. This makes it a great choice for organizations that prioritize sustainability and want to minimize their impact on the environment.

In addition to its effectiveness in suppressing fires, the NOVEC 1230 Fire Suppression System is also easy to install and maintain. It is designed to be user-friendly, with clear instructions and minimal maintenance requirements. This means that customers can enjoy peace of mind knowing that their property is protected without having to worry about complicated maintenance procedures.

In conclusion, the NOVEC 1230 Fire Suppression System is a reliable and effective solution for protecting against fire hazards. Its perfluorohexone fire extinguishing system and FK-5-1-12 agent make it a powerful tool for suppressing fires, while its user-friendly design and environmental friendliness make it a great choice for organizations that prioritize sustainability. Whether you are looking to protect a commercial, industrial, or residential property, the NOVEC 1230 Fire Suppression System is a smart choice that you can trust.

## Features:

Product Name: NOVEC 1230 Fire Suppression System Nominal Pressure: 2.5MPa Maximum filling weight: 170.4kg Cylinder Capacity: 120L Size(mm): 500\*450\*1900 Color: Yellow Uses FK-5-1-12 fire suppression system Also known as FK-5-1-12 Automatic fire extinguishing system Automatic fire extinguishing system

#### **Technical Parameters:**

Product Name	Perfluorohexone cabinet fire extinguishing system (Novec 1230)
Manufacturer	Over 20-years manufacturer of FK-5-1-12 automatic fire extinguishing equipment
Size(mm)	500*450*1900
Maximum Filling Weight	170.4kg
Discharge Time	10 Seconds
Spraying Time	≤10s
Cylinder Material	Steel
Cylinder Capacity	120L
Nominal Pressure	2.5MPa
Maximum Protection Capacity	192m <sup>3</sup>
Protected Zone Range	Proportion: ≤500m <sup>2</sup> Volume: ≤1600m <sup>3</sup>

## **Applications:**

This product is manufactured in Guangzhou, Guangdong, China, and it has been certified by CE, CCC, ISO, CMA, CAL, and CNAS. The minimum order quantity for this product is 1 set, and the price is negotiable. The packaging details include a plywood outer box with bubble bag or paper, and the delivery time is 5~10 working days.

The payment terms for this product include L/C, T/T. The supply ability for this product is 3000 sets per week, making it readily available for customers who need it.

The RUIGANG YF120/2.5N-RG NOVEC 1230 Fire Suppression System is designed to provide maximum protection capacity of 192m<sup>3</sup>, and its spraying time is less than or equal to 10 seconds. The cylinder material for this product is steel, and it comes in a yellow color. The maximum filling weight for this product is 170.4kg.

This cabinet automatic fire extinguishing system is suitable for scenarios where there is a high risk of fire such as power distribution rooms, communication rooms, archives, and control rooms. It is also ideal for use in areas with valuable equipment or documents that need to be protected from fire damage.

The RUIGANG YF40/2.5N-RG NOVEC 1230 Fire Suppression System is an effective and reliable product that can help prevent and control fires in enclosed spaces. It is a must-have product for anyone who wants to ensure the safety of their property and equipment. Whether you need an automatic fire extinguishing system for your home or office, this product is the right choice for you.

#### **Customization:**

Our minimum order quantity is 1 set, and we offer competitive pricing with flexible payment terms, including L/C, T/T. Our packaging details consist of a plywood outer box with a bubble bag or paper, and we offer a supply ability of 3000 sets per week. Our delivery time is 5~10 working days. As a manufacturer with over 20 years of experience, we take pride in providing high-quality and customizable fire suppression systems to meet your specific needs. If you're looking for a reliable and effective Novec 1230 Automatic Fire Suppression System, contact us today to discuss your customization options. Product Attributes: Brand Name: RUIGANG Model Number: YF120/2.5N-RG Place of Origin: Guangzhou, Guangdong, China Certification: CE/CCC/ISO/CMA/CAL/CNAS Minimum Order Quantity: 1 set Price: negotiation Packaging Details: Plywood outer box with bubble bag or paper Delivery Time: 5~10 working days Payment Terms: L/C, T/T Supply Ability: 3000 sets per week Color: Yellow Size(mm): 500\*450\*1900 Activation Method: Electric/Manual Cylinder Capacity: 120L Company Type: Manufacturer Over 20-years

## **Support and Services:**

Installation guidance and technical support 24-hour emergency service

## **Packing and Shipping:**

Product Packaging:

The NOVEC 1230 Fire Suppression System is packaged in a sturdy cardboard box with foam inserts to ensure safe transportation and handling. The box is labeled with product information and handling instructions for easy identification and safe storage. Shipping:

We ship the NOVEC 1230 Fire Suppression System using a reputable carrier to ensure fast and reliable delivery. The product is carefully packaged to prevent any damage during shipping. Shipping costs will vary based on location and quantity ordered.

