

Novec 1230 Automatic Fire Extinguishing System Cylinder Volume 90L

Our Product Introduction

for more products please visit us on firefm200.com

Basic Information

- Place of Origin: Guangzhou, Guangdong, China
- Brand Name: RUIGANG
- Certification: CE/CCC/ISO/CMA/CAL/CNAS
- Model Number: YF90/2.5N-RG
- Minimum Order Quantity: 1 set
- Price: negotiation
- Packaging Details: Plywood outer box with bubble bag or paper
- Delivery Time: 5~10 working days
- Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card
- Supply Ability: 3000 sets per week



Product Specification

- Cylinder Material: Steel
- Working Temperature: -10°C 50°C
- Cylinder Volume: 90L
- Size(mm): 500*450*1600
- Maximum Filling Weight: 127.8kg
- Company Type: Manufacturer Over 20-years
- Cylinder Capacity: 90L
- Nominal Pressure: 2.5MPa
- Discharge Time: ≤10s
- Maximum Protection Volume: 144m³
- Highlight: 90l novtec 1230,
90l automatic fire extinguishing system,
1230 novtec 1230

Product Description

127.8kg Filled Steel Cylinder 90L Automatic fire extinguishing system

Product Description:

The fire suppression system has a cylinder volume of 90L, which provides sufficient capacity to extinguish fires in large areas. The system uses FK-5-1-12 automatic fire extinguishing equipment, which is a clean agent that is environmentally friendly and safe for humans. This agent is a perfluorohexone that is ideal for use in applications that require a fast and effective response to fires. The NOVEC 1230 Fire Suppression System has a discharge time of 10 seconds, which is a critical factor in preventing the spread of fires. The system is designed to quickly deploy the FK-5-1-12 agent, which quickly extinguishes the fire and prevents it from spreading to other areas. This ensures that the fire is contained and that damage to property and assets is minimized. The FK-5-1-12 automatic fire extinguishing equipment used in the NOVEC 1230 Fire Suppression System is a highly effective agent that has been extensively tested and proven to be reliable in a wide range of applications. This clean agent does not leave any residue or damage to property, making it an ideal choice for use in sensitive areas such as data centers, museums, and hospitals. In summary, the NOVEC 1230 Fire Suppression System is a high-quality product that provides reliable and efficient fire protection. The system uses FK-5-1-12 automatic fire extinguishing equipment, which is a clean agent that is environmentally friendly and safe for humans. The system has a cylinder volume of 90L, a discharge time of 10 seconds, and is manufactured by a company with over 20 years of experience in the industry.

Features:

Product Name: NOVEC 1230 Fire Suppression System
Cylinder Capacity: 90L
Spraying Time: ≤10s
Agent Type: Clean Agent
Maximum filling weight: 127.8kg
FK-5-1-12 automatic fire extinguishing equipment
FK-5-1-12 Automatic fire extinguishing system
Novec 1230 fire suppression system

Technical Parameters:

Cylinder Material	Steel
Protected Zone Range	Proportion: ≤500m ² Volume: ≤1600m ³
Feature	Clean Gas And Environmental Friendly
Discharge Time	10 Seconds
Cylinder Volume	90L
Agent Type	Clean Agent
Maximum filling weight	127.8kg
Maximum protection capacity	144m ³
Company Type	Manufacturer Over 20-years
Working Temperature	-10°C 50°C

This is technical parameters of Novec 1230 cabinet automatic fire extinguishing equipment, which is also named as Perfluorohexone fire extinguishing system or Perfluorohexone automatic fire extinguishing system.

Applications:

The RUIGANG YF90/2.5N-RG is a Novec 1230 fire suppression system that is designed to handle fire emergencies in various scenarios. The product is manufactured in Guangzhou, Guangdong, China and is certified with CE, CCC, ISO, CMA, CAL, and CNAS. It has a minimum order quantity of 1 set and is priced through negotiation.

The product comes with packaging details that include a plywood outer box with bubble bags or paper. Delivery time is estimated at 5-10 working days, and payment terms include L/C, D/P, T/T, Western Union, Paypal, and Credit card. This product has a supply ability of 3000 sets per week.

The RUIGANG YF90/2.5N-RG is an automatic fire extinguishing system that utilizes the clean agent FK-5-1-12. It is suitable for protecting zones with a proportion range of ≤500m² and a volume range of ≤1600m³. The discharge time for this product is 10 seconds, making it a fast and efficient solution for fire emergencies.

This product is available in a yellow color, making it easy to spot in case of emergencies. It is suitable for various scenarios such as computer rooms, archives, communication centers, and other places where valuable equipment needs to be protected. The Novec 1230 cabinet fire extinguishing system is also suitable for use in museums, art galleries, and other areas where valuable artifacts are stored.

The RUIGANG YF90/2.5N-RG is a reliable perfluorohexone automatic fire extinguishing system that is suitable for use in various scenarios. It is an effective solution for fire emergencies, and its clean agent makes it safe for use in areas where people are present. Its yellow color makes it easily noticeable, and it comes with various certifications that guarantee its quality.

If you are looking for a reliable FK-5-1-12 cabinet fire extinguishing system, the RUIGANG YF90/2.5N-RG is an excellent choice. Contact us today to place your order and enjoy the benefits of a fast and efficient fire suppression system.

Customization:

Product Customization Services:

Brand Name: RUIGANG

Model Number: YF90/2.5N-RG

Place of Origin: Guangzhou, Guangdong, China

Certification: CE/CCC/ISO/CMA/CAL/CNAS

Minimum Order Quantity: 1 set

Price: negotiation

Packaging Details: Plywood outer box with bubble bag or paper

Delivery Time: 5~10 working days

Payment Terms: L/C, D/P, T/T, Western Union, Paypal, Credit card

Supply Ability: 3000 sets per week

Cylinder Volume: 90L

Color: Yellow

Cylinder Material: Steel

Agent Type: Clean Agent

Protected Zone Range: Proportion: $\leq 500\text{m}^2$ Volume: $\leq 1600\text{m}^3$

Keywords: FK-5-1-12 Automatic fire extinguishing system, FK-5-1-12 automatic fire extinguishing equipment, cabinet automatic fire extinguishing system

Support and Services:

The NOVEC 1230 Fire Suppression System is a clean agent fire protection system designed to quickly extinguish fires in enclosed areas. The system works by releasing a fine mist of NOVEC 1230 gas which rapidly cools and suppresses the fire, preventing re-ignition. Our technical support team is available to assist with any questions or issues related to installation, maintenance, and operation of the NOVEC 1230 Fire Suppression System. We also offer training services to ensure proper use and handling of the system. In addition, we provide regular maintenance services to ensure the system is functioning properly and in compliance with all relevant regulations and standards. This includes inspections, testing, and refilling of the NOVEC 1230 agent.

Packing and Shipping:

Product Packaging:

The NOVEC 1230 Fire Suppression System will be packaged in a sturdy cardboard box.

The box will be labeled with the product name and any necessary safety information.

The system components will be securely packed with protective materials to prevent any damage during shipping.

Shipping:

The NOVEC 1230 Fire Suppression System will be shipped via ground transportation.

Shipping times may vary depending on the destination.

A tracking number will be provided once the system has shipped.

Please inspect the package upon arrival and contact us immediately if there are any issues.



Guangzhou Ruigang Fire-Fighting Equipment Co., Ltd.



+86 18124226119



18124226119@139.com



firefm200.com

No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou