



FM200 Cabinet Fire Extinguishing System For Fire Suppression

Basic Information

• Place of Origin: Guangzhou, Guangdong, China

• Brand Name: RUIGANG

CCC/ISO9001/ISO45001/ISO14001/ISO10012 · Certification:

• Model Number: GQQ40/2.5RG GQQ70/2.5RG

> GQQ90/2.5RG GQQ100/2.5RG GQQ120/2.5RG GQQ150/2.5RG

GQQ180/2.5RG

Minimum Order

Quantity:

1 set

Price: negotiation

· Packaging Details: We pack products with first polyfoam and

> then the wooden cases. Once products are too big or customers require a pallet for products, we will make products a pallet.

• Delivery Time: 10~15 working days

• Payment Terms: L/C, T/T,

• Supply Ability: 30000 sets / month



Product Specification

· Installation: Easy To Install

• Max Working Pressure: 4.2MPa

· Cabinet Material: Steel

• Working Temperature: 0°C ~ 50°C

• Extinguishing Agent: FM200

• Discharge Pressure: 5.6±0.28MPa

Pattern Of Extinguishing • Fire Protection Level:

· Spray Time: 10 Seconds • Filling Density: 1120kg/m3 · Filling Agent: 40kg~180kg • Power: DC24V 50Hz

• Highlight: FM200 Cabinet Fire Extinguishing System,

Effective Cabinet Fire Extinguishing System

Product Description:

The FM200 extinguishing system has a maximum working pressure of 4.2MPa, which ensures that the extinguishing agent is released at a high velocity and covers the entire protected area quickly. This extinguishing system uses a pattern of extinguishing that is designed to suppress fires rapidly, minimizing damage to property and equipment.

One of the advantages of the FM200 Cabinet Fire Extinguishing System is its ease of installation. The system can be installed quickly and easily in any enclosed space, and it does not require any major modifications to the existing infrastructure. This makes it an ideal fire protection solution for retrofit projects or buildings with limited space.

The FM200 Cabinet Fire Extinguishing System can operate in a wide range of temperatures, from 0°C to 50°C. This means that the system can provide reliable fire protection even in harsh environments, where other fire protection systems may not be suitable. The cabinet of the FM200 Cabinet Fire Extinguishing System is made of steel, which provides excellent durability and protection against physical damage. The steel cabinet also ensures that the extinguishing system is protected from environmental factors such as moisture and dust, which can affect the performance of the system.

In summary, the FM200 Cabinet Fire Extinguishing System is an advanced fire protection solution that uses HFC-227ea as the fire extinguishing agent. This system is easy to install, has a maximum working pressure of 4.2MPa, and can operate in a wide range of temperatures. The steel cabinet provides excellent protection against physical damage and environmental factors, making it a reliable and durable fire protection solution for enclosed spaces.

Applications:

With CCC/ISO9001/ISO45001/ISO14001/ISO10012 certification, this product is designed to meet international standards. Customers can order a minimum of one set and negotiate the price with the manufacturer. The packaging includes first polyfoam and then wooden cases, and if the products are too big or need a pallet, the manufacturer will provide one. The delivery time is 10-15 working days, and the payment terms include L/C and T/T. The supply ability is 30,000 sets per month.

The FM200 Cabinet Fire Extinguishing System is perfect for various occasions and scenarios. It is suitable for computer rooms, communication rooms, data centers, archives, museums, and other places that contain valuable objects that need protection. It is also ideal for power distribution rooms and production sites that use flammable and explosive materials. The product's pollution-free feature makes it an excellent choice for places that require clean air or where pollution is a concern.

The RUIGANG FM200 Cabinet Fire Extinguishing System works on the pattern of extinguishing, and its cabinet color is red. The system can be activated manually or automatically, depending on the requirements of the customer. The extinguishing agent used in this product is FM200, which is a clean and non-toxic gas that does not damage the environment. The electrical requirements of the product are 220V and 50Hz, making it easy to install and use.

Support and Services:

The FM200 Cabinet Fire Extinguishing System is designed to protect sensitive and valuable equipment from fire damage. It uses a clean agent, FM200, to suppress fires quickly and effectively without leaving any residue or damage to the equipment. The system is easy to install, operate, and maintain, and can be customized to fit the specific needs of your equipment and environment.

Our technical support and services for the FM200 Cabinet Fire Extinguishing System include:

System design and engineering

Guide installation and debugging

Training for operators and maintenance personnel

Periodic inspections and maintenance

Emergency service and repair

We are committed to ensuring the safety and protection of your equipment and property. Our team of experienced technicians and engineers are available to provide you with the support and services you need to keep your FM200 Cabinet Fire Extinguishing System operating at peak performance.

Packing and Shipping:

Product Packaging:

1 FM200 Cabinet Fire Extinguishing System

Instruction Manual

Mounting Hardware

Shipping Information:

Shipping Method: ocean shipping









No. 2, Zhongwei Road, Dongyong Town, Nansha District, Guangzhou